







ARM TYPE	REVEAL	DIM. A
O	1 1/16" TO 2"	12 1/4"
OZ	2 1/8" TO 5"	12 1/2"
OZA	5 1/8" TO 8"	12 3/4"



NOTES

1. REINFORCE METAL DOORS AND FRAMES PER ANSI A250.8 & SDI-100, 12 GAUGE RECOMMENDED.
2. LEFT HAND DOOR SHOWN, RIGHT HAND OPPOSITE.
3. TURN LEVER USED WITH 690 & 590 SERIES HOLDERS ONLY, 690 TURN LEVER MAY BE INSTALLED ON EITHER SIDE OF DOOR.
4. FOR 1536-1539 INSTALLATION, SEE TEMPLATES A7485 - A7487.
5. FOR 1546-1549 INSTALLATION, SEE TEMPLATES A7488 - A7490.
6. FOR 697-699 INSTALLATION, SEE TEMPLATES A7482 - A7484.
7. FOR 597-599 INTALLATION, SEE TEMPLATES A7479 - A7481.



SARGENT® Manufacturing Company
100 Sargent Drive New Haven, CT 06511

DATA SHEET: 281 SERIES CLOSER (LOW
CEILING/TOP JAMB APPLICATION) WITH O,
OZ OR OZA ARM AND 1536-1539, 1546-1549,
OR 597-599 OR 697-699 HOLDER OR STOP

RELEASE DATE
12 JULY 02
TEMPLATE NO.
A7520 A