

EXIT DEVICE	DIM. A	DIM. B	DIM. C
9706, 9713, 9715 9710X SCREWLESS ROSE INACTIVE KNOB	2 5/8	1 5/16	2 1/8
9728, 9762, 9763	3 1/8	1 3/8	1 1/2
9710	NO CUT-OUT REQ'D.		

USED WITH
ALL FUNCTIONS

IF LOCK STILE IS 4 1/2" WIDE
OR WIDER DIM = 2 3/4" IF LOCK
STILE IS UNDER 4 1/2" DIM =
1/2 OF STILE

FOURTEEN #10-24 TAPPED
HOLES. WE RECOMMEND
THAT THESE HOLES BE
DRILLED AND TAPPED
IN THE FIELD

APPROX. EQUAL

THIS DIMENSION WILL VARY
WITH STOP HEIGHT AND
DOOR CLEARANCE
SEE ILLUSTRATION

(H) 1 13/16" FOR 881
MONITOR STRIKE
(SEE NOTE #2)

TOP STRIKE #619
SEE TEMPLAT
NO. 4009

Ø OF CYLINDER

IF AN OUTSIDE CYLINDER
IS TO BE USED, MAKE
A 1 3/8 DIA. HOLE
THRU DOOR (NOT REQ'D FOR
060R13 FUNCTION WHEN "ET"
CONTROL OR 300 SERIES
AUX. CONTROL IS USED)

①

LOCATION OF TOP
THRU BOLT FOR
OUTSIDE GRIP IF
USED

43 1/8 FROM
FINISHED FLOOR
(CROSS BAR 36"
FROM FLOOR)

IF 626 OR 627
STRIKES ARE USED
DIM. D = 15/16

IF SARGENT 9700
THRESHOLD OR
623 STRIKE IS
USED DIM. D = 1 3/16

(H) ② FOR MOUNTING LOCATION & RELATED INFO. OF 881
MONITOR STRIKE SEE TEMPLATE 4387.

① TOLERANCE ON FRACTIONAL
DIMENSIONS ± 1/64.

SARGENT & COMPANY

NEW HAVEN, CONN. 06509

TEMPLAT: 9700 SERIES EXIT DEVICE
FOR 9700, 13-9700,
14-9700 & 16-9700 VERTICAL
ROD EXIT DEVICES

RELEASE DATE
28 OCT. 98
TEMPLAT NO.
4010J