

EXIT DEVICE	DIM. A	DIM. B	DIM. C
9706, 9713, 9715	2 ⁵ / ₈	1 ⁵ / ₆	2 ¹ / ₈
9728, 9762, 9763	3 ¹ / ₈	1 ³ / ₈	1 ¹ / ₂
9710	NO CUT-OUT REQD.		

TEN # 10-24 TAPPED HOLES. WE RECOMMEND THAT THESE HOLES BE DRILLED AND TAPPED IN THE FIELD

APPROX. EQUAL

43 ¹/₈ FROM FINISHED FLOOR. (CROSS BAR 36" FROM FLOOR)

INSIDE OF DOOR

IF LOCK STILE IS 4 ¹/₂ WIDE OR WIDER DIM. = 2 ³/₄ IF LOCK STILE IS UNDER 4 ¹/₂ DIM. = ¹/₂ OF STILE

THIS DIMENSION WILL VARY WITH STOP HEIGHT AND DOOR CLEARANCE. SEE ILLUSTRATION

FOUR ⁷/₃₂ DIA HOLES THRU THIS SIDE OF DOOR ONLY

Ø OF CYLINDER

IF AN OUTSIDE CYLINDER IS TO BE USED, MAKE A 1 ³/₈ DIA HOLE THRU DOOR

LOCATION OF TOP THRU BOLT FOR OUTSIDE GRIP IF USED

DIM. D

(H) 1 ¹³/₁₆" FOR 881 MONITOR STRIKE (SEE NOTE # 2)

TOP STRIKE #619 SEE TEMPLAT NO. 4009

IF 626 OR 627 STRIKES ARE USED DIM. D = 15 ¹⁵/₁₆

IF SARGENT 9700 THRESHOLD OR 623 STRIKE IS USED DIM. D = 1 ³/₁₆

(H) ② FOR MOUNTING LOCATION & RELATED INFO. OF 881 MONITOR STRIKE SEE TEMPLATE 4387.

① TOLERANCE ON FRACTIONAL DIMENSIONS ± 1 ¹/₆₄.

SARGENT & COMPANY

NEW HAVEN, CONN. 06509

METAL DOOR TEMPLAT FOR 9700, 13-9700, 14-9700 & 16-9700 VERTICAL ROD EXIT DEVICES BY THRU BOLTED OUTSIDE TRIM

RELEASE DATE 29 NOV 89 TEMPLAT NO. 4018H