

RECOMMENDED EDWARDS 120V AC SIGNALING DEVICES

FOR USE WITH CATALOG NUMBER 910 PHONE PAGE™

Catalog Number	Device Description	Voltage Rating	Current Rating	Mounting Method(s)
STANDARD APPLICATIONS -- INDOOR USE				
<u>BELLS</u>				
340-4N5**	Adaptabel - 4" Vibrating	120V ac, 50/60 Hz	0.06 amp.	Direct Wall Mount
340-6N5**	Adaptabel - 6" Vibrating	120V ac, 50/60 Hz	0.07 amp.	Direct Wall Mount
340-10N5**	Adaptabel - 10" Vibrating	120V ac, 50/60 Hz	0.07 amp.	Direct Wall Mount
<u>HORNS/SIRENS</u>				
874-N5	Adaptahorn	120V ac, 50/60 Hz	0.13 amp.	Direct Wall Mount
5520-N5**	Duotronic Horn/Siren	120V ac, 50/60 Hz	0.35 amp.	Direct Wall Mount
5530-N5**	Adaptatone See NOTE (5)	120V ac, 50/60 Hz	0.38 amp.	Direct Wall Mount
STANDARD APPLICATIONS -- INDOOR/OUTDOOR USE				
<u>LIGHTS</u>				
49*-N5	Adaptabeacon Flashing Light with Dust Cover	120V ac, 60 Hz	0.22 amp.	Direct or Pipe Mount
50*-N5	Adaptabeacon Flashing Light	120V ac, 60 Hz	0.22 amp.	Direct or Pipe Mount
52*-N5	Adaptabeacon Rotating Light	120V ac, 60 Hz	0.26 amp.	Direct or Pipe Mount
92*-N5	Adaptabeacon Strobe Light	120V ac, 60 hz	0.10 amp.	Direct or Pipe Mount
<u>HORNS</u>				
876-N5	Adaptahorn	120V ac, 50/60 Hz	0.13 amp.	Direct Wall Mount
<p>* Specify - amber (A), blue (B), clear (C), green (G) or red (R) lens. ** Also suitable for outdoor use when used with required Edwards weatherproof back box.</p>				

Catalog Number	Device Description	Voltage Rating	Current Rating	Mounting Method(s)
EXPLOSIONPROOF APPLICATIONS -- INDOOR USE				
	<u>LIGHTS</u>			
52EX*-N5	Adaptabeacon Rotating Light See NOTE (1)	120V ac, 50/60 Hz	0.26 amp.	Pipe Mount
	<u>BELLS</u>			
340EX-6N5	Adaptabel - 6" Vibrating See NOTE (2)	120V ac, 50/60 Hz	0.04 amp.	Direct Wall Mount
340EX-8N5	Adaptabel - 8" Vibrating See NOTE (2)	120V ac, 50/60 Hz	0.04 amp.	Direct Wall Mount
340EX-10N5	Adaptabel - 10" Vibrating See NOTE (2)	120V ac, 50/60 Hz	0.04 amp.	Direct Wall Mount
	<u>HORNS</u>			
878EX-N5	Adaptahorn See NOTE (2)	120V ac, 60 Hz	0.13 amp.	Direct Wall Mount
5533-N5	Adaptatone, Two Signal See NOTES (3) and (5)	120V ac, 60 hz	0.38 amp.	Direct Wall Mount
5534-N5	Adaptatone, Two Signal See NOTES (4) and (5)	120V ac, 60 hz	0.38 amp.	Direct Wall Mount
<p>* Specify - amber (A), blue (B), clear (C), green (G) or red (R) lens. ** Also suitable for outdoor use when used with required Edwards weatherproof back box.</p>				

NOTES

- (1) UL Listed for Class I, Groups C and D; Class II, Groups E, F and G; Class III locations.
- (2) UL Listed for Class I, Groups B, C and D; Class II, Groups E, F and G; Class III locations.
- (3) UL Listed for Class I, Groups B, C and D.
- (4) UL Listed for Class I, Groups C and D; Class II, Groups E, F and G; Class III locations.
- (5) Tone input connections must be jumped.

- WARNING -

SPECIAL PRECAUTIONS MUST BE TAKEN WHEN WIRING EXPLOSIONPROOF SIGNALING DEVICES IN HAZARDOUS ENVIRONMENTS. CONSULT THE NATIONAL ELECTRICAL CODE FOR SPECIFIC INFORMATION REGARDING PROPER WIRING METHODS AND MATERIALS.