





# SARGENT®

## ASSA ABLOY



Centerline of  
Hinge or Pivot


**NOTE:** These installation instructions to be used for product manufactured on or after Nov. 1, 2013.  
Date Code: KU Shipped with arm as shown.



Mfg.  
Date: KU

| Arm | Reveal                      |
|-----|-----------------------------|
| JO  | To 3-0 (76)                 |
| JOZ | 2-3/4 (70) to 6-3/4 (171.5) |

| Fastener Type       | Matl. | Drill Sizes                             |
|---------------------|-------|-----------------------------------------|
| Self Drill Screw    | Metal | No drill required                       |
|                     | Wood  | 3/16" Predrill                          |
| 1/4 - 20 Mach Screw | Metal | #7 Drill; 1/4-20 Tap                    |
| Sleeve Nuts & Bolts | Metal | 9/32" Thru<br>3/8" Face opposite closer |
|                     | Wood  | 3/8" Thru                               |



- Do not scale drawing.
- Left hand door shown, right hand opposite.
- Dimensions are in inches / (mm)
- Hollow metal door require channel or box type reinforcement when through bolt mount is specified.
- Sex bolts required for wood or plastic faced fire door mounting.
- Minimum thickness recommended for reinforcements in hollow metal doors and frames: .146" (2.66mm) unless otherwise specified.
- Maximum width hinge for this template is 5" (127).

Copyright © 2013, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.

ASSA ABLOY, the global leader  
in door opening solutions

SARGENT® Manufacturing Company

DATA SHEET:  
1331 DOOR CLOSER WITH JO, JOZ  
ARM. TOP JAMB ARM FOR  
STANDARD AND DEEP REVEAL  
APPLICATIONS..

RELEASE DATE:  
8/20/2013

TEMPLATE NO.  
A8165A